




Premium Translucent Series

XF 7T Transluzente Serie: Transluzente, polymere Premium-Farbfolien für die Leuchtwerbung

XF 7T Translucent Series: Translucent, polymeric signmaking vinyls for illuminated signage

7214 Gelb Yellow		7271 Weinrot Wine Red		7227 Blassblau Pale Blue		7221 Violett Violet	
7254 Schwefelgelb Sulphur Yellow		7275 Pink Pink		7278 Mittelblau Medium Blue		7237 Dunkelviolet Dark Violet	
7204 Kadmiumgelb Cadmium Yellow		7246 Lindgrün Pastel Green		7217 Azurblau Azure Blue		7230 Braun Brown	
7244 Goldgelb Golden Yellow		7226 Gelbgrün Yellow Green		7207 Lichtblau Light Blue		7219 Telegrau Tele Grey	
7218 Hellorange Bright Orange		7222 Signalgrün Signal Green		7247 Blau Blue		7209 Grau Grey	
7208 Orange Orange		7236 Minzgrün Mint Green		7233 Blau-Violett Violet Blue		7266 Signalweiss Signal White	
7261 Feuerrot Soft Red		7276 Dunkelgrün Dark Green		7267 Königsblau Royal Blue		7216 Weiss White	
7251 Verkehrsrot Traffic Red		7277 Türkisblau Turquoise Blue		7212 Ultramarineblau Ultramarine Blue		7215 Schwarz Black	
7210 Rubinrot Ruby Red		7268 Wasserblau Water Blue		7257 Nachtblau Midnight Blue		7299 Gold Gold	



Premium Translucent Series

Produkteigenschaften

Materialstärke (Folie):	80µm
Obermaterial:	Transuzente, polymer weichgemachte Spezial-PVC-Folie (kalandriert)
Klebstoff:	Permanenter, lösemittelfreier druckaktivierbarer Acrylat-Klebstoff (UV-stabilisiert)
Klebkraft:	≥12N/25mm, nach FINAT/FTM1 (24h)
Abdeckpapier:	120g/m² Spezial-Kraftabdeckpapier mit roten Karolinien für einfaches Verarbeiten & Positionieren
Haltbarkeit im Außeneinsatz:	bis zu 7 Jahre
Verklebetemperatur:	mind. +10°C
Geeignete Untergründe:	Flache (Acryl-) Glasflächen, z.B. Fensterscheiben, Leuchtkästen etc.
Anwendungsgebiete:	Hochwertige Leuchtwerbung, hinterleuchtete (Acryl-) Glasflächen im Innen- und Außenbereich, effektvolle Beschriftungen
Besonderheiten:	Seidenmattes Finish (reflexionsarme Oberfläche) Gleichmäßige Einfärbung sowohl im Auflicht als auch in der Hinterleuchtung Ausgezeichnete Verarbeitungseigenschaften und Dimensionsstabilität Schwerentflammbarkeitszertifikat: B1 (DIN 4102)

Product Features

Caliper (face film):	80 micron (3.2mil)
Face film:	Translucent, special polymeric vinyl film (calendered)
Adhesive:	Permanent clear, solvent-free pressure-sensitive acrylic adhesive (UV-stabilised)
Adhesive strength:	≥12N/25mm, acc. to FINAT/FTM1 (24h)
Release liner:	120gsm special clay-coated silicone paper with red squared print for easy processing & positioning
Outdoor durability:	up to 7 years
Application temperature:	min. +10°C
Suitable substrates:	Flat (acrylic) glass surfaces, e.g. shopping windows, light boxes etc.
Application areas:	Decoration and identification of internally illuminated / backlit signs made from glass, acrylic, etc. indoors and outdoors
Special features:	Premium satin finish (reduced surface gloss inhibits undesired reflection) Provides homogenous and reliable colour uniformity and stability Excellent processing properties and first class dimensional stability Non-flammable acc. to DIN 4102 B1

Abmessungen / Available dimensions

630mm/1260mm x 10m/25m/50m

x-film Selbstklebefolien GmbH

Gerberstrasse 2
51789 Lindlar/Germany
☎ +49/(0)2266-47785-0
☎ +49/(0)2266-47785-440
✉ sales@x-film.com
www.x-film.com

